



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1193384	16	5/8	25	0,99	3	45	9	135	0,37	0,25	120	400
1156209	19	3/4	28	1,10	3	45	9	135	0,42	0,28	120	400
1185810	25	1	35	1,38	3	45	9	135	0,62	0,42	120	400
1172271	32	1-1/4	43	1,69	3	45	9	135	0,86	0,58	120	400
1168070	38	1-1/2	49	1,93	3	45	9	135	1,00	0,67	120	400
1170619	51	2	63,5	2,50	3	45	9	135	1,51	1,01	120	400
1168150	63,5	2-1/2	77,5	3,05	3	45	9	135	2,04	1,37	120	400
1156950	76	3	90	3,55	3	45	9	135	2,41	1,62	120	400
1168169	90	3-35/64	104	4,10	3	45	9	135	2,81	1,89	120	400
1168126	102	4	116	4,57	3	45	9	135	3,15	2,12	120	400
1170651	127	5	143	5,63	3	45	9	135	4,18	2,81	120	400
1172280	152	6	170	6,70	3	45	9	135	5,91	3,97	120	400



IT

## IT Tubo per acqua e gas di scarico

**Norme:** SAE J 2006 R1.

**Applicazione:** tubo cord per passaggio acqua di raffreddamento del motore e gas di scarico.

**Temperatura:** da -30 a +80°C.

**Costruzione**

**Sottostrato:** nero, liscio, in gomma sintetica.

**Rinforzo:** tessuti sintetici ad alta resistenza.

**Copertura:** nera, liscia (ad impressione tela), in gomma sintetica, resistente agli agenti atmosferici.

EN

## EN Water and wet exhaust delivery hose

**Standards:** SAE J 2006 R1.

**Application:** softwall hose used to convey water, in cooling engine systems and for wet exhaust.

**Temperature:** from -30°C (-22°F) to +80°C(+176°F).

**Construction**

**Tube:** black, smooth, synthetic rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish), synthetic rubber, weathering resistant.

FR

## FR Tuyau pour eau et gaz d'échappement

**Normes:** SAE J 2006 R1.

**Applications:** tuyau nappé textile pour refoulement d'eau de refroidissement dans le moteur marin et gaz d'échappement.

**Gamme de températures:** de -30°C à +80°C.

**Construction**

**Tube:** caoutchouc synthétique noir lisse.

**Armature:** nappes synthétiques très résistantes.

**Revêtement:** caoutchouc synthétique noir lisse (aspect bandelé) résistant aux agents atmosphériques.

DE

## DE Wasser- und Abgasschlauch

**Normen:** SAE J 2006 R1.

**Verwendung:** Druckschlauch zur Förderung von Motorkühlwasser und Abgas.

**Temperaturbereich:** -30°C bis +80°C.

**Aufbau**

**Seele:** synthetischer Gummi, schwarz, glatt.

**Einlagen:** hochzähes synthetisches Cordgewebe.

**Decke:** synthetischer Gummi, schwarz, glatt (stoffgemustert), witterungsbeständig.